# **HSR-10**

# 1-11/16" High Speed Radial Cement Bond Logging Tool

## **Description**

The High Speed Radial (HSR) tool evaluates the cement bond quality and integrity to both pipe and formation by providing the measurements of the cement bond amplitude (CBL) through near receiver (3-ft crystal), and variable density log (VDL) through far receiver (5-ft Crystal). HSR tool also provide a cement map through six segmented receivers, each segment covers 60° section of the pipe. All sonic data is captured and stored digitally within 2ms after the transmitter fires allowing flexibility of the output telemetry. This tool is easily configured to customers requirements. The separate acquisition and output module allows changes to the output telemetry to be easily accomplished.

# **Applications**

- Evaluation of cement bond quality and integrity.
- Location of free-pipe and cement-top.
- 360° cement map.

## **Features**

- Rated for High-temperature and high-pressure environments.
- Gamma ray detector, CCL detector, and temperature sensor are built in.
- Compatible with most surface systems.
- Runs on all standard wirelines.
- Combines with two standard pulse tools on the bottom
- All receivers are built in a slotted housing to provide rigidity, strength, and noise isolation.
- Rigid design ideal for horizontal logging
- Electronic design verified for 1 hour operation at 415°F to ensure reliability.
- Easy to service and maintain.

## **Specifications**

Tool Operating Voltage	100 to 150 VDC	Tool Length	4.475 m (14 feet, 8 inches)
Tool Operating Current	80 to 90 MA	Tool Weight	33.0 Kg (73 Lb)
Tool Time Cycle	3 X 50ms = 150ms	Tool Positioning	Must be centralized
Max. Temperature	204°C (400°F)	Max Logging Speed	Up to 30m/min (100 ft/min)
Max. Pressure	172.4 Mpa (25,000 PSI)	Borehole Fluids	Oil - Fresh Water - Brine
Receivers	Near & Far = 1.2 " Omni Radial = 6 Segments	Measurements	Near @ 3 ft, Far @ 5 ft Radial @ 2 ft
Transmitter	1.2 " Dia. Omni	Recommended Max. Casing ID	177.8 mm (7.00 in)
Tool Diameter - OD	42.8 mm(1-11/16 in)	Recommended Min. Casing ID	50.8 mm(2.0 in)



**Downhole Sonic Solutions Inc.** 

170, 5255 McCall Way N.E. Calgary, AB, T2E 7J5, Canada Phone: +1 403-219-2108 Fax: +1 403-219-2106

www.dsstools.com sales@dsstools.com